



MC coupling

	MC00	MC038	MC042	MC048	MC058	MC070	MC075	MC085
TaperFix Bush Size:Pin Half			1610	2012	2817	3020		3535
TaperFix Bush Size:Bush Half			1210	1610	2012	2517		300
Maximum Bore:TaperFix Pin Half			42	50	65	75		90
Maximum Bore:TaperFix Bush Half			32	42	50	65		75
Maximum Bore:Pilot Bore Pin Half	38	42	48	55	65	80	85	90
Maximum Bore:Pilot Bore bush Half	30	38	42	48	58	70	75	85
ØD-Outside Diameter	127	132	146	171	193	216	254	279
ØH-Hub Diameter:Pin Halves	64	70	82	94	110	132	142	162
ØH-Hub Diameter:Bush Halves	51	64	70	82	97	117	127	147
L-Length:MC	88	102	118	128	142	159	183	207
L-Length:MCT			56	63	82	102		172
M-Gap	6	6	6	6	6	7	7	7
R-Flange Length:Pin Halves	12	12	12	17	17	17	30	30
R-Flange Length:Bush Halves	26	26	26	3	33	33	56	56
T-Length Through Bore:MC Pin&Bush Halves	41	48	56	61	68	76	88	100
T-Length Through Bore:MCT Pin Halves			25	2	44	51		89
T-Length Through Bore:MCT Bush Halves			25	25	32	44		76
Number of Pin	4	6	8	6	8	10	8	10
Pin Size	GC1-3	GC1-3	GC1-3	GC1.3/4-3	GC1.3/4-3	GC1.3/4-3	GC2.3/4-3	GC2.3/4-3
Ring Size:Rubber	GC1-4	GC1-4	GC1-4	GC1.3/4-4	GC1.3/4-5	GC1.3/4-6	GC2.3/4-4	GC2.3/4-4
Ring Size:Polyurethane	U272	U272	U272	U273	U273	U273	U274	U274